

# SN-TPT6436HZ-M

Thermal & Optical Bi-spectrum Heavy Duty PTZ Camera



## Key Features

- VOx uncooled focal plane detector with 640x512 resolution
- NETD  $\leq$  40mK
- 75/100 mm motorized focus thermal lens optional
- 32x/60x optical zoom visible lens optional
- Support human/vehicle detection and fire point detection
- Smart events: intrusion, single line crossing, double line crossing, loitering, wrong-way, people counting, enter area, leave area
- Support 3 temperature measurement rule types (spot, line, area)
- Temperature measurement range:  $-20^{\circ}\text{C} \sim 150^{\circ}\text{C}$  ( $-4^{\circ}\text{F} \sim 302^{\circ}\text{F}$ )
- Power off self-locking, strong wind resistance
- NDAA Compliance, Anti-frozen, IP66

# Specification

Thermal Module	
Image Sensor	Uncooled VOx Focal Plane Arrays
Resolution	Sensor is 640x512. Image can be scaled up to 1280x1024
Pixel Pitch	12µm
NETD	≤ 40 mK
Spectral Range	8 ~ 14 um
Image Setting	Brightness, Sharpness, Contrast, Mirror, FFC control, 2D/3D DNR
Pseudo-color Setting	White-hot/Black-hot/Rainbow/Ironbow etc. up to 17 modes
Thermal Lens	
Focus Control	Motorized Focus
Focal Length	75 mm                      100mm
Aperture	F1.0                              F1.0
Angle of View	H: 6°, V:5°                      H: 4.3°, V:3.5°
Detection Distance (Fire: 1*1m)	3125 m                              4167 m
Detection Distance (Human: 1.8*0.5m)	3121 m                              4161 m
Detection Distance (Vehicle: 4*1.5m)	9583 m                              12778 m
Recognition Distance (Human: 1.8*0.5m)	780 m                                1040 m
Recognition Distance (Vehicle: 4*1.5m)	2396 m                              3194 m
Optical Module	
Image Sensor	1/2.8" CMOS
Max. Resolution	2592 (H)x1520 (V), 4MP
Shutter Speed	1/5 ~ 1/20,000s
Min. Illumination	Color: 0.03 Lux @ (F1.6, AGC ON), B/W: 0.003 Lux
WDR	True WDR
Focal Length	12.5 ~ 400mm (15.6 ~ 500mm, 12.5 ~ 750mm, 16.7 ~ 1000mm optional)
Aperture	F2.5 ~ F16
Angle of View	H: 33° ~ 1.7°
Optical Zoom	32x (32x, 60x, 60x optional)
Focus Control	Auto/Manual
Mirror	Support
Defog	Support, and optical defog
Privacy Masking	Support
PTZ	
Pan/Tilt Range	Pan: 0° ~ 360° endless, Tilt: +45° ~ -45°
Pan/Tilt Speed	Pan: 0.01° ~ 30°/s, Tilt: 0.01° ~ 15°/s
Wiper	Support
Preset Accuracy	± 0.1°
Presets	400
Scan	8 scans, up to 32 presets per scan
Patrol	12 patrols, up to 32 presets per scan
Track	6 tracks
3D Positioning	Support
Speed Setup	Auto/Manual (0-8)
Power Off Memory	Support
Idle Motion	It can activate Preset/ Scan/Tour/Pattern if there is no command in the specified period

Video and Audio	
Main Stream	Thermal: 1280x1024, 1280x720, 640x512 @ 25/30fps Optical: 2560x1520, 1920x1080, 1280x720 @25/30fps
Sub Stream	Thermal: D1, CIF @ 25/30fps Optical: D1, VGA, 640x360, CIF, QVGA @25/30fps
Bit Rate Control	CBR/VBR
Bit Rate	Thermal: Main stream: 100Kbps~8Mbps Sub stream: 100Kbps~6Mbps Optical: Main stream: 200Kbps~12Mbps, Sub stream: 100Kbps~6Mbps
Region of Interest	Off/On (8 Zone, Rectangle)
Audio Compression	G711: 8kbps, RAW_PCM: 16kbps
Smart Function	
Smart Alarm	Motion detection, Disk alarm, I/O alarm, IVS alarm, Temperature detection & alarm
Smart Detection	Support human/vehicle detection and fire point detection, (ship detection optional)
Intelligent Analysis	Intrusion, Single line crossing, Double line crossing, Loitering, Wrong-way, Enter area, Leave area (these 7 function support accurate detection of people/vehicles), People counting
Temperature Detection	
Temperature Detection	3 temperature measurement rule types, 20 rules in total, 1 full screen, 19 others (spot, areas, line).
Temperature Alarm	Over temperature alarm, Temperature difference alarm
Accuracy	±2℃ / ±2%
Response Time	≤ 30ms
Temperature Range	-20℃ to 150℃ (-4°F to 302°F), -20℃ to 550℃ (-4°F to 1022°F) Customizable
Network	
Protocols	IPv4/IPv6 ,HTTP,RTSP/RTP/RTCP, TCP/UDP, DHCP, DNS, PPPOE, SMTP, 802.1x
Interoperability	ONVIF, CGI, SDK
Max. User Access	10 Users
Web Viewer	<IE11, Chrome, Firefox, Microsoft Edge
Web Language	English, Chinese, Polish, Italian, Portuguese, Spanish, Russian, French, Czech, Hungarian
Interface	
Network Interface	1 Ethernet (10/100 Base-T) RJ-45 Connector
Audio Interface	2ch Audio In,2ch Audio Out
Alarm Interface	3ch Alarm In,3ch Alarm Out
RS485	Support
BNC Output	Support
Reset Button	Support (Built-in)
SD Card Slot	Built-in, up to 256GB
General	
Power Supply	DC36V
Power Consumption	Max 150 W
Working Temperature	-40℃~60℃ (-40°F~140°F)
Storage Conditions	0 ~ 90% RH
Certifications	CE /FCC
Ingress Protection	IP66
Casing	Metal
Dimensions	730 x 443 x 636mm (28.74x17.44x25.04 inch)
Net Weight	≤ 48Kg (105.8 lb)

## Dimensions (mm)

